

View Online at <https://aerobasegroup.com/nsn/5910-01-206-5824>

Body Style:

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.1000

Terminal Length:

0.620 inches

Body Length:

2.800 inches

Body Width:

1.810 inches

Body Height:

2.205 inches

Terminal Diameter:

0.190 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.243 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.445 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.810 inches

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting studs

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

100000.0 megohms

Capacitance Value Per Section:

20.000 microfarads single section

Nonderated Operating Temp:

71.0 degrees celsius

Thread Size:

0.164 inches

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

25.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

1.0 ac-rms single section

Tolerance Range Per Section:

-10.00/+10.00 microfarads single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.5000

Terminal Surface Treatment:

Copper

Dielectric Material:

Plastic

Test Data Document:

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0