

View Online at <https://aerobasegroup.com/nsn/5910-01-206-5824>

**Body Style:**

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.1000

**Terminal Length:**

0.620 inches

**Body Length:**

2.800 inches

**Body Width:**

1.810 inches

**Body Height:**

2.205 inches

**Terminal Diameter:**

0.190 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.243 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.445 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.810 inches

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

4 threaded mounting studs

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

100000.0 megohms

**Capacitance Value Per Section:**

20.000 microfarads single section

**Nonderated Operating Temp:**

71.0 degrees celsius

**Thread Size:**

0.164 inches

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

25.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

1.0 ac-rms single section

**Tolerance Range Per Section:**

-10.00/+10.00 microfarads single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.5000

**Terminal Surface Treatment:**

Copper

**Dielectric Material:**

Plastic

**Test Data Document:**

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0