## NSN 5910-01-206-9908

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-206-9908

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.020 inches

**Body Length:** 

0.100 inches

**Body Width:** 

0.100 inches

**Body Height:** 

0.100 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

0.100 inches

**Terminal Height From Body:** 

1.500 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

50.0 megohms

**Capacitance Value Per Section:** 

4.700 picofarads single section

**Nonderated Operating Temp:** 

0.100 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

80.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

**Case Material:** 

Ceramic

**Insulation Resistance At Reference Temp:** 

1250.0 megohm-microfarads

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-206-9908

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Shelf L	₋ife:
---------	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0