## NSN 5910-01-207-3497

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-207-3497

**Body Style:** 

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

**Terminal Length:** 

0.922 inches

**Body Length:** 

Between 2.875 inches and 2.968 inches

**Body Width:** 

Between 1.875 inches and 1.968 inches

**Body Height:** 

Between 4.438 inches and 4.562 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

1.375 inches

**Terminal Diameter:** 

0.216 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.375 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**End Application:** 

Missile, air launch cruise (alcm) agm-86b

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Mounting Facility Type And Quantity:** 

2 threaded mounting studs

**Capacitance Value Per Section:** 

15.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 90.0 degrees celsius

**Thread Size:** 

0.216 inches

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 ac-rms single section and 400.0 dc single section

**Criticality Code Justification:** 

Feat

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Metal

**Dissipation Factor At Reference Tempurature In Percent:** 

0.400

## NSN 5910-01-207-3497

Paper Dielectric Fixed Capacitor - Page 2 of 2



Special	Features:
---------	-----------

Weapon system essential

**Terminal Type And Quantity:** 

2 standoff, threaded stud

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A010b0