Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-207-3497

Body Style:

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.922 inches

Body Length:

Between 2.875 inches and 2.968 inches

Body Width:

Between 1.875 inches and 1.968 inches

Body Height:

Between 4.438 inches and 4.562 inches

Center To Center Distance Between Terminals Parallel To Length:

1.375 inches

Terminal Diameter:

0.216 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.375 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Missile, air launch cruise (alcm) agm-86b

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

2 threaded mounting studs

Capacitance Value Per Section:

15.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 90.0 degrees celsius

Thread Size:

0.216 inches

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 ac-rms single section and 400.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00 to 10.00 percent single section

Case Material:

Metal

Dissipation Factor At Reference Tempurature In Percent:

0.400



Special Features:

Weapon system essential

Terminal Type And Quantity:

2 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0