# NSN 5910-01-207-8903

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-207-8903

**Body Style:** W/mtg tabs/flanges terminals on opposite surfaces **Reliability Indicator:** Not established **Terminal Length:** Between 0.600 inches and 0.680 inches **Body Length:** 2.800 inches **Body Width:** 2.780 inches **Body Height:** 1.810 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.310 inches **Terminal Diameter:** 0.190 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.190 inches and 2.210 inches **Schematic Diagram Designator:** No common or grounded electrode (s) Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.190 inches and 2.210 inches **Internal Electrical Connection Type:** Extended foil **Mounting Facility Screw Thread Series Designator:** Unc **Mounting Facility Type And Quantity:** 4 threaded mounting studs **Section Quantity:** 2 **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 20.000 microfarads all sections

# **Nonderated Operating Temp:**

Between -45.6 degrees celsius and 71.0 degrees celsius

### **Thread Size:**

0.164 inches

# Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc all sections

### **Tolerance Range Per Section:**

-10.00/+10.00 percent all sections

NSN 5910-01-207-8903 Plastic Dielectric Fixed Capacitor - Page 2 of 2



Case Material:
Metal
nsulation Resistance At Reference Temp:
25000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.500
Dielectric Material:
Plastic
Case Insulation Material:
Plastic
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A010b0