

View Online at <https://aerobasegroup.com/nsn/5910-01-208-1963>

**Body Style:**

Chip type

**Reliability Indicator:**

Not established

**Terminal Length:**

0.010 inches

**Body Length:**

0.125 inches

**Body Width:**

0.060 inches

**Body Height:**

0.060 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Forrestal class cv; tarawa class lha; arleigh burke class ddg; nimitz class cvn; wasp class lhd; austin ship class lpd-4 amphibious transport docks; emory s.Land class as; supply class aoe; whidbey island class lsd; ticonderoga class cg (47)

**Capacitance Value Per Section:**

1000.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-15.0/+15.0 with rated voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Ceramic

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

3.0000

**Terminal Surface Treatment:**

Solder

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 bonding pad

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0