NSN 5910-01-208-5243

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-208-5243				
Body Style:				
W/o mtg facilities terminal (s) on one surface				
Reliability Indicator:				
Not established				
Terminal Length:				
0.236 inches				
Body Length:				
0.709 inches				
Body Width:				
0.413 inches				
Body Height:				
0.177 inches				
Center To Center Distance Between Terminals Parallel To Length:				
0.591 inches				
Terminal Diameter:				
0.032 inches				
Schematic Diagram Designator:				
No common or grounded electrode (s)				
Capacitance Value Per Section:				
0.047 microfarads single section				
Nonderated Operating Temp:				
Between -40.0 degrees celsius and 85.0 degrees celsius				
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:				
400.0 single section				
Nonderated Continuous Voltage Rating And Type Per Section:				
250.0 dc single section				
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:				
-200.0 to 200.0 single section				
Tolerance Range Per Section:				
-5.00 to 5.00 percent single section				
Case Material:				
Plastic				
Insulation Resistance At Reference Temp:				
10000.0 megohms				
Dissipation Factor At Reference Tempurature In Percent:				
0.5000				
Terminal Surface Treatment:				
Solder				
Terminal Type And Quantity:				
2 uninsulated wire lead				

N/a

Shelf Life:

NSN 5910-01-208-5243

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	nit	O+	Measure:
u		v	wicasuic.

--

Demilitarization:

No

Fiig:

A010b0