NSN 5910-01-208-7263

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-208-7263

view Offiline at https://acrobasegroup.com/histi/03/10-01-200-//203
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
2.000 inches
Body Length:
0.530 inches
Body Width:
0.160 inches
Body Height:
0.260 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Alarm set, anti-intrusion, restricted area an/gss-26a
Insulation Resistance At Maximum Operating Temp:
4000.0 megohms
Capacitance Value Per Section:
0.390 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-5.00 to 5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
40000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5910-01-208-7263

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0