

View Online at https://aerobasegroup.com/nsn/5910-01-208-9617

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.0100

#### **Terminal Length:**

1.625 inches

#### **Body Diameter:**

Between 0.562 inches and 0.582 inches

**Body Length:** 

1.125 inches

**Terminal Diameter:** 

0.040 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

### **Capacitance Value Per Section:**

1.000 microfarads single section

### Nonderated Operating Temp:

Between -65.0 degrees celsius and 100.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.1500

## **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-83421/1 government specification

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0