## NSN 5910-01-209-2752

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-209-2752

#### **Body Style:**

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

## **Reliability Indicator:**

Not establishednot establishednot established

#### **Terminal Length:**

0.750 inches 0.750 inches 0.750 inches

#### **Body Diameter:**

0.440 inches

#### **Body Length:**

0.680 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

0.200 inches

#### **Terminal Diameter:**

0.020 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Anode Type:

Solid

#### Impedance At Minimum Operating Tempurature In Ohms:

0.3

## **Electrical Polarization:**

Polarized

#### Capacitance Value Per Section:

330.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

6.3 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### Case Material:

Plastic

#### **Capacitive Electrode Material:**

Tantalum

#### **Dissipation Factor At Reference Tempurature In Percent:**

10.0000

#### Dc Leakage At Reference Temp:

20.000 microamperes

## **Terminal Surface Treatment:**

Solder

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-01-209-2752

Electrolytic Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0