## NSN 5910-01-209-4461

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-209-4461

**Body Style:** 

W/o mtg facilities, terminals on opposite surfaces

Reliability Indicator:

Not established

**Terminal Length:** 

0.500 inches

**Body Length:** 

Between 0.120 inches and 0.150 inches

**Body Width:** 

Between 0.030 inches and 0.100 inches

**Body Height:** 

Between 0.095 inches and 0.126 inches

**Terminal Diameter:** 

0.016 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

100000.0 megohms

**Capacitance Value Per Section:** 

0.900 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-30.0 to 30.0 single section

**Tolerance Range Per Section:** 

-5.00 to 5.00 percent single section

**Case Material:** 

Ceramic or glass

**Insulation Resistance At Reference Temp:** 

1000000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.150

**Terminal Surface Treatment:** 

Silver

**Precious Material And Location:** 

Terminals silver

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-209-4461

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:
•	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0