NSN 5910-01-209-4512

Mica Dielectric Fixed Capacitor - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5910-01-209-4512 |
|--|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Length: |
| 0.390 inches |
| Body Width: |
| 0.380 inches |
| Body Height: |
| 0.220 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.141 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 10000.0 megohms |
| Capacitance Value Per Section: |
| 400.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: |
| +0.0 to 70.0 single section |
| Tolerance Range Per Section: |
| -2.00 to 2.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.0100 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |

N/a

Shelf Life:

NSN 5910-01-209-4512

Mica Dielectric Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0