NSN 5910-01-209-4517

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-209-4517

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

0.375 inches 0.375 inches 0.375 inches

Body Diameter:

1.020 inches

Body Length:

1.150 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.300 inches and 0.400 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

Two terminals common to one electrode

Anode Type:

Plain foil

Impedance At Minimum Operating Tempurature In Ohms:

0.044

Electrical Polarization:

Polarized

Capacitance Value Per Section:

1200.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

80.00

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

3 pin

NSN 5910-01-209-4517

Electrolytic Fixed Capacitor - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0