NSN 5910-01-209-4544

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-209-4544 **Body Style:** Piston **Overall Length:** 0.240 inches **Terminal Length:** 0.205 inches **Body Length:** 0.240 inches **Overall Diameter:** 0.094 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 4000.0 **Terminal Width:** 0.040 inches **Terminal Thickness:** 0.008 inches **Inclosure Type:** Encased **Terminal Location:** Circumference bent backward **Adjustment Device Torque:** Between 0.200 inch-ounces and 2.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Insulation Dc Resistance At Max Operating Temp:** 100000.0 megohms **Mounting Facility Type And Quantity:** 1 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +0.3/+1.2 single section **Nonderated Voltage Rating And Type:** 500.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw

Capacitance Drift In Picofarads:

0.02 single section

NSN 5910-01-209-4544

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal	Type	And	Quantity	y:
----------	------	-----	----------	----

1 printed circuit

Specification Data:

81349-mil-c-14409/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0