NSN 5910-01-210-1181

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-210-1181 **Body Style:** Piston **Overall Length:** 1.235 inches **Terminal Length:** 0.500 inches **Body Length:** 1.155 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -150.0/+150.0 single section Center To Center Distance Between Terminals Parallel To Length: 1.075 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.234 inches **Terminal Diameter:** 0.030 inches **Quality Factor At 25 Deg Celsius:** 250.0 **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Mounting Facility Type And Quantity:** 4 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0/+42.0 single section **Nonderated Voltage Rating And Type:** 1000.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Capacitance Drift In Picofarads: 0.05 single section **Terminal Type And Quantity:** 4 wire lead Shelf Life:

N/a

NSN 5910-01-210-1181

Glass Dielectric Variable Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A096a0