

View Online at <https://aerobasegroup.com/nsn/5910-01-210-7654>

Body Style:

W/mtg tabs/flanges terminals on opposite surfaces

Reliability Indicator:

Not established

Terminal Length:

0.375 inches

Body Length:

2.405 inches

Body Height:

1.000 inches

Terminal Diameter:

0.072 inches

Unthreaded Mounting Hole Diameter:

0.211 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.885 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.572 inches

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

0.300 picofarads single section

Nonderated Operating Temp:

Between -45.6 degrees celsius and 71.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

2000.0 dc single section

Temperature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

-100.0 to 300.0 single section

Tolerance Range Per Section:

-5.00 to 5.00 picofarads single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.50000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-39001 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0