NSN 5910-01-210-9744

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-210-9744 |
|---|
| Body Style: |
| W/o mtg facilities, terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Terminal Length: |
| 0.520 inches |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Body Length: |
| Between 2.100 inches and 2.220 inches |
| Body Width: |
| Between 1.250 inches and 1.370 inches |
| Body Height: |
| Between 2.560 inches and 2.680 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 5.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 70.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 370.0 ac-rms single section |
| Tolerance Range Per Section: |
| -10.00 to 10.00 percent single section |
| Case Material: |
| Metal |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.100 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 quick disconnect, male, four blade |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5910-01-210-9744

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0