## NSN 5910-01-210-9750

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-210-9750

## **Body Style:**

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

#### **Reliability Indicator:**

Not establishednot established

## **Terminal Length:**

0.281 inches 0.281 inches 0.281 inches

#### **Body Diameter:**

Between 3.000 inches and 3.062 inches

#### **Body Length:**

Between 5.594 inches and 5.718 inches

#### **Center To Center Distance Between Terminals Parallel To Diameter:**

1.250 inches

#### **Terminal Diameter:**

0.190 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

## **Impedance At Minimum Operating Tempurature In Ohms:**

0.014

#### **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

8500.000 microfarads single section

#### **Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### **Case Material:**

Metal

## **Capacitive Electrode Material:**

Aluminum

## **Equivalent Series Resistance At Reference Tempurature In Ohms:**

0.029

## Dc Leakage At Reference Temp:

6.000 milliamperes

#### **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 threaded hole

## Shelf Life:

N/a

# NSN 5910-01-210-9750

Electrolytic Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0