## NSN 5910-01-211-4817

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-211-4817

Body	Stv	٠ ما
Douv	JLY	ıc.

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.197 inches and 0.236 inches

**Body Length:** 

Between 0.507 inches and 0.517 inches

**Body Width:** 

Between 0.349 inches and 0.359 inches

**Body Height:** 

Between 0.152 inches and 0.162 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.379 inches and 0.409 inches

**Terminal Diameter:** 

0.031 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

0.150 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

10000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.000

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-01-211-4817

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0