## NSN 5910-01-211-5020



Glass Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-211-5020 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.125 inches **Body Diameter:** 0.219 inches **Body Length:** 0.938 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** Radio set an/grc-206 **Capacitance Value Per Section:** 1100.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 105.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -25.0 to 25.0 single section **Tolerance Range Per Section:** -5.00 to 5.00 percent single section Case Material: Glass **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.0010 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

N/a
Unit Of Measure:

## NSN 5910-01-211-5020

Glass Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0