## NSN 5910-01-211-9889

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-211-9889

| Body Style:   |
|---|
| W/o mtg facilities, axial terminals                                   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 1.250 inches  |
| Body Diameter:  |
| 0.090 inches  |
| Body Length:  |
| 0.250 inches  |
| Terminal Diameter:  |
| Between 0.015 inches and 0.027 inches                                 |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)                                   |
| Features Provided:  |
| Burn in   |
| Insulation Resistance At Maximum Operating Temp:                      |
| 10000.0 megohms   |
| Capacitance Value Per Section:  |
| 0.010 microfarads single section                                      |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -15.0 to 15.0 without voltage applied single section                  |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 125.0 degrees celsius               |
| Nonderated Continuous Voltage Rating And Type Per Section:            |
| 100.0 dc single section   |
| Tolerance Range Per Section:  |
| -10.00 to 10.00 percent single section                                |
| Case Material:  |
| Plastic   |
| Insulation Resistance At Reference Temp:                              |
| 100000.0 megohms  |
| Dissipation Factor At Reference Tempurature In Percent:               |
| 2.500   |
| Terminal Surface Treatment:   |
| Solder  |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |
| Shelf Life:   |
| N/a   |

--

**Unit Of Measure:** 

## NSN 5910-01-211-9889

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0