

View Online at <https://aerobasegroup.com/nsn/5910-01-211-9896>

Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

Between 2.250 inches and 2.250 inches and 2.250 inches and 2.750 inches 2.750 inches 2.750 inches

Body Diameter:

0.910 inches

Body Length:

Between 3.125 inches and 3.343 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.150 inches and 0.450 inches

Terminal Diameter:

Between 0.038 inches and 0.048 inches

Schematic Diagram Designator:

Two common terminals for each electrode

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Capacitance Value Per Section:

850.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

760.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.15

Dc Leakage At Reference Temp:

126.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

4 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0