

View Online at <https://aerobasegroup.com/nsn/5910-01-212-4231>

Body Style:

W/thd mtg hol (s)/stud(s), terminal(s) on one surface/w/thd mtg hole(s)/stud(s), terminal(s) on one surface/w/thd mtg hole(s)/stud(s), terminal(s) on one surface

Reliability Indicator:

Not established/not established/not established

Terminal Length:

2.125 inches 2.125 inches 2.125 inches

Body Length:

1.125 inches

Body Width:

0.938 inches

Body Height:

1.844 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Section Quantity:

4

Capacitance Value Per Section:

30.000 microfarads all sections

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc all sections

Tolerance Range Per Section:

-15.00/+50.00 percent all sections

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Temperature In Percent:

20.000

Dc Leakage At Reference Temp:

2.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

8 insulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0