

View Online at <https://aerobasegroup.com/nsn/5910-01-212-4231>

**Body Style:**

W/thd mtg hol (s)/stud(s), terminal(s) on one surface/w/thd mtg hole(s)/stud(s), terminal(s) on one surface/w/thd mtg hole(s)/stud(s), terminal(s) on one surface

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

2.125 inches 2.125 inches 2.125 inches

**Body Length:**

1.125 inches

**Body Width:**

0.938 inches

**Body Height:**

1.844 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Section Quantity:**

4

**Capacitance Value Per Section:**

30.000 microfarads all sections

**Nonderated Operating Temp:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc all sections

**Tolerance Range Per Section:**

-15.00/+50.00 percent all sections

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Power Factor At Reference Temperature In Percent:**

20.000

**Dc Leakage At Reference Temp:**

2.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

8 insulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0