

View Online at <https://aerobasegroup.com/nsn/5910-01-212-5669>

Body Style:

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Unable To Decode:

Unable to decode and unable to decode

Terminal Length:

Between 0.150 inches and 0.170 inches

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Body Length:

Between 1.590 inches and 1.650 inches

Body Width:

Between 0.460 inches and 0.500 inches

Body Height:

Between 2.810 inches and 2.870 inches

Center To Center Distance Between Terminals Parallel To Length:

1.200 inches

Center To Center Distance Between Terminals Parallel To Width:

0.100 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

5865-01-145-5197 countermeasures set

Section Quantity:

3

Capacitance Value Per Section:

94.000 microfarads 3rd section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc 2nd section

Tolerance Range Per Section:

-10.00/+75.00 percent all sections

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0