

View Online at <https://aerobasegroup.com/nsn/5910-01-212-5669>

**Body Style:**

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:**

Not established

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Length:**

Between 0.150 inches and 0.170 inches

**Unable To Decode:**

Unable to decode and unable to decode

**Unable To Decode:**

Unable to decode and unable to decode

**Body Length:**

Between 1.590 inches and 1.650 inches

**Body Width:**

Between 0.460 inches and 0.500 inches

**Body Height:**

Between 2.810 inches and 2.870 inches

**Center To Center Distance Between Terminals Parallel To Length:**

1.200 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.100 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**End Application:**

5865-01-145-5197 countermeasures set

**Section Quantity:**

3

**Capacitance Value Per Section:**

94.000 microfarads 3rd section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

75.0 dc 2nd section

**Tolerance Range Per Section:**

-10.00/+75.00 percent all sections

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

6 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0