## NSN 5910-01-213-0760

**Body Style:** 

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-213-0760

Rotary **Terminal Length:** 0.177 inches **Overall Height:** 0.091 inches **Shaft Diameter:** 0.080 inches single shaft **Shaft Length:** 0.020 inches single shaft **Overall Diameter:** 0.126 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.134 inches **Quality Factor At 25 Deg Celsius:** 1000.0 **End Application:** 5820-01-180-8943 an/prc-68a **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 0.200 inch-ounces and 1.500 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000.0 megohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius **Shaft Type:** Round, slotted single shaft Capacitance Range In Picofarads: +5.0 to 35.0 single section Nonderated Voltage Rating And Type: 25.0 dc continuous single section Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: -4.50 to 2.50 and -2.50 to 2.00 single section **Adjustment Device Drive Type And Quantity:** 1 shaft

Capacitance Drift In Picofarads:

0.50 single section

## NSN 5910-01-213-0760

Ceramic Dielectric Variable Capacitor - Page 2 of 2



<b>Terminal</b>	Type	And	Quantity:
-----------------	------	-----	-----------

2 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A096a0