NSN 5910-01-213-0761

Ceramic Dielectric Variable Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-01-213-0761



Body Style: Rotary **Terminal Length:** 0.177 inches **Overall Height:** 0.091 inches **Shaft Diameter:** 0.080 inches single shaft **Shaft Length:** 0.020 inches single shaft **Overall Diameter:** 0.126 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.134 inches **Quality Factor At 25 Deg Celsius:** 1000.0 **End Application:** 5820-01-180-8943 an/prc-68a **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 0.200 inch-ounces and 1.500 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000.0 megohms **Mounting Facility Type And Quantity:** 2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Shaft Type:

Round, slotted single shaft

Capacitance Range In Picofarads:

+2.0 to 10.0 single section

Nonderated Voltage Rating And Type:

25.0 dc continuous single section

Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius:

-4.50 to 2.50 and -2.50 to 2.00 single section

Adjustment Device Drive Type And Quantity:

1 shaft

Capacitance Drift In Picofarads:

0.50 single section

NSN 5910-01-213-0761

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Termi	nal	Type	And	Qua	ntity:
2 tab,	sol	der Iu	ıg		

z tab, solder ta

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0