# NSN 5910-01-213-1328

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-213-1328

Radv	Style:
Doug	JUNIO.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

#### **Reliability Indicator:**

Not establishednot established

### **Terminal Length:**

0.250 inches 0.250 inches 0.250 inches

**Body Diameter:** 

2.578 inches

# **Body Length:**

4.250 inches

#### **Center To Center Distance Between Terminals Parallel To Diameter:**

1.125 inches

#### **Terminal Diameter:**

0.190 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

### **Anode Type:**

Plain foil

#### **Electrical Polarization:**

Polarized

# **End Application:**

6625-01-137-5369 signal generator

### **Capacitance Value Per Section:**

1000.000 microfarads single section

# **Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

450.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### **Case Material:**

Metal

### **Capacitive Electrode Material:**

Aluminum

### **Equivalent Series Resistance At Reference Tempurature In Ohms:**

0.197

# Dc Leakage At Reference Temp:

4.000 milliamperes

# **Case Insulation Material:**

Plastic

### **Terminal Type And Quantity:**

2 threaded hole

# NSN 5910-01-213-1328

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0