Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-214-5428

# **Body Style:**

W/o mtg facilities terminal (s) on one surface

- **Reliability Indicator:**
- Not established
- **Terminal Length:**
- 1.000 inches
- Body Length:
- 0.450 inches

#### **Body Width:**

0.305 inches

**Body Height:** 

0.150 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.194 inches and 0.256 inches

#### **Terminal Diameter:**

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

# Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

# **Capacitance Value Per Section:**

6.000 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

# Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

-200.0 to 200.0 single section

#### **Tolerance Range Per Section:**

-0.50 to 0.50 percent single section

#### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.001

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

Mica Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0