

View Online at <https://aerobasegroup.com/nsn/5910-01-214-8952>

Body Style:

Cylindrical

Overall Length:

0.410 inches

Terminal Length:

0.125 inches

Overall Diameter:

0.312 inches

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Center To Center Distance Between Terminals Parallel To Height:

0.280 inches

Terminal Diameter:

0.040 inches

Quality Factor At 25 Deg Celsius:

800.0

Inclosure Type:

Encapsulated

Terminal Location:

Circumference on end opposite adjustment control perpendicular

Adjustment Device Torque:

Between 0.500 inch-ounces and 5.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+1.5/+20.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Test Data Document:

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 pin and 1 printed circuit

Specification Data:

81349-mil-c-14409/17 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0