NSN 5910-01-215-3136

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-215-3136

Body	Style:

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

0.063 inches 0.063 inches

Body Diameter:

1.400 inches

Body Length:

2.187 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.500 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Amplifier, radio am-7061/wsc-6

Capacitance Value Per Section:

2800.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

9.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

55.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.0087

Dc Leakage At Reference Temp:

1.500 microamperes

Case Insulation Material:

Plastic

NSN 5910-01-215-3136

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:	
2 threaded hole	
Shelf Life:	
N/a	
Unit Of Measure:	

Demilitarization:

No

Fiig:

A010b0