

View Online at <https://aerobasegroup.com/nsn/5910-01-215-3937>

**Thread Class:**

2a

**Body Style:**

Plate-meshing

**Overall Length:**

1.062 inches

**Bushing Diameter:**

0.250 inches

**Overall Height:**

Between 0.500 inches and 0.524 inches

**Overall Width:**

Between 0.421 inches and 0.445 inches

**Bushing Length:**

0.250 inches

**Body Length:**

Between 0.531 inches and 0.593 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

45.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-15.0 to 15.0 single section

**Mounting Facility Screw Thread Series Designator:**

Unef

**Inclosure Type:**

Encased

**Tuning Characteristic:**

Straight line capacity single section

**Adjustment Device Torque:**

Between 2.500 inch-ounces and 10.000 inch-ounces

**Bushing Shape:**

Round

**Plate Air Gap:**

0.010 inches

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thread Size:**

0.250 inches

**Capacitance Range In Picofarads:**

+1.4 to 9.2 single section

**Nonderated Voltage Rating And Type:**

650.0 ac peak single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Precious Material And Location:**

All metal surfaces silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0