## NSN 5910-01-215-4640

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-215-4640

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Terminal Length:
0.500 inches 0.500 inches 0.500 inches
Body Diameter:
0.374 inches
Body Length:
0.531 inches

0.200 inches

**Terminal Diameter:** 

0.016 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Solid

**Impedance At Minimum Operating Tempurature In Ohms:** 

**Center To Center Distance Between Terminals Parallel To Diameter:** 

1.2

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

15.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

35.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Plastic

**Capacitive Electrode Material:** 

Tantalum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

8.0000

Dc Leakage At Reference Temp:

5.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-215-4640

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0