NSN 5910-01-215-7917

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-215-7917

Body	Stv	le٠
Bouv	JLV	ıc.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

25.0 millimeters 25.0 millimeters 25.0 millimeters

Body Diameter:

5.0 millimeters

Body Length:

11.0 millimeters

Center To Center Distance Between Terminals Parallel To Diameter:

2.0 millimeters

Terminal Diameter:

0.5 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

6625-01-146-5801 oscilloscope

Capacitance Value Per Section:

1.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-15.00/+15.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Tempurature In Percent:

0.4000

Equivalent Series Resistance At Reference Tempurature In Ohms:

3.00

Dc Leakage At Reference Temp:

4.000 microamperes

Terminal Surface Treatment:

Solder

NSN 5910-01-215-7917 Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:		
Plastic		
Terminal Type And Quantity:		
2 uninsulated wire lead		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		

A010b0