

View Online at <https://aerobasegroup.com/nsn/5910-01-216-0113>

**Body Style:**

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

Between 0.032 inches and 0.032 inches and 0.032 inches and 0.094 inches 0.094 inches 0.094 inches

**Body Diameter:**

Between 1.969 inches and 2.031 inches

**Body Length:**

Between 5.563 inches and 5.687 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.859 inches and 0.891 inches

**Terminal Diameter:**

0.190 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Etched foil

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

20000.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

40.0 dc single section

**Tolerance Range Per Section:**

-10.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dc Leakage At Reference Temp:**

6.000 microamperes

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0