

View Online at <https://aerobasegroup.com/nsn/5910-01-216-0266>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not established/not established/not established

Terminal Length:

Between 0.218 inches and 0.218 inches and 0.218 inches and 0.282 inches 0.282 inches 0.282 inches

Body Diameter:

Between 3.000 inches and 3.110 inches

Body Length:

Between 8.563 inches and 8.813 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 1.172 inches and 1.266 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Capacitance Value Per Section:

220000.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 65.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

40.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.008

Dc Leakage At Reference Temp:

13.000 milliamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0