

View Online at <https://aerobasegroup.com/nsn/5910-01-216-1879>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not established/not established/not established

Terminal Length:

0.375 inches 0.375 inches 0.375 inches

Body Diameter:

0.413 inches

Body Length:

0.927 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.200 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

0.33

Electrical Polarization:

Polarized

End Application:

1270-01-190-1676 point-target su

Capacitance Value Per Section:

150.000 microfarads single section

Nonrated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonrated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.88

Dc Leakage At Reference Temp:

11.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0