NSN 5910-01-216-2277

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-216-2277 **Body Style:** Rotary **Terminal Length:** 3.0 millimeters **Overall Height:** 5.5 millimeters **Overall Diameter:** 5.2 millimeters Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 600.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -300.0 to 300.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 5.1 millimeters **Err Default:** 1.0 millimeters **Terminal Thickness:** 0.2 millimeters **End Application:** 6625-01-146-5801 oscilloscope **Inclosure Type: Encased Adjustment Device Torque:** Between 30.0 centimeter-grams and 140.0 centimeter-grams **Insulation Dc Resistance At Max Operating Temp:** 10000.0 megohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -25.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +2.8 to 12.0 single section **Nonderated Voltage Rating And Type:** 250.0 ac continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a **Unit Of Measure:**

--

NSN 5910-01-216-2277

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0