NSN 5910-01-216-6382

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-216-6382

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Mounting Slot Width:

0.266 inches

Body Length:

Between 2.610 inches and 2.702 inches

Body Width:

Between 2.032 inches and 2.156 inches

Body Height:

Between 3.594 inches and 3.718 inches

Center To Center Distance Between Terminals Parallel To Length:

1.500 inches

Terminal Diameter:

0.216 inches

Terminal Height From Body:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.250 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

2 mounting slots

Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

Capacitance Value Per Section:

0.003 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 70.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

7000.0 dc single section

Tolerance Range Per Section:

-10.00 to 10.00 percent single section

Case Material:

Glass

Insulation Resistance At Reference Temp:

7500.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.100

Terminal Type And Quantity:

2 standoff, threaded stud

NSN 5910-01-216-6382

Mica Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:
-------	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0