## NSN 5910-01-216-6384

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-216-6384 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.700 inches **Body Width:** 0.300 inches **Body Height:** 0.200 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.375 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Insulation Resistance At Maximum Operating Temp:** 1500.0 megohm-microfarads **Capacitance Value Per Section:** 0.022 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 25000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyester

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-216-6384

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0