NSN 5910-01-216-6632

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-216-6632

D	_	٦,		0	٠			
D	u	u	v	J	ιν	ш	e:	

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

0.250 inches 0.250 inches 0.250 inches

Body Diameter:

1.453 inches

Body Length:

2.250 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.500 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

6625-01-069-5959 test set, electra

Capacitance Value Per Section:

95.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

15000.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

350.0 dc single section

Tolerance Range Per Section:

-1.00/+1.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

1.50

Dc Leakage At Reference Temp:

6000.000 microamperes

Case Insulation Material:

Plastic

NSN 5910-01-216-6632

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 threaded hole
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0