NSN 5910-01-216-7232

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-216-7232

Body Style: Dual inline Reliability Indicator: Not established **Terminal Length:** Between 0.120 inches and 0.176 inches **Body Length:** Between 0.787 inches and 0.795 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.250 inches **Center To Center Distance Between Terminals Parallel To Width:** Between 0.300 inches and 0.400 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 4920-01-118-3584 interface test **Section Quantity: Capacitance Value Per Section:** 1.000 microfarads all sections **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -56.0 to 22.0 without voltage applied all sections **Nonderated Operating Temp:** Between 10.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc all sections **Tolerance Range Per Section:** -20.00 to 20.00 percent all sections Case Material: **Plastic Insulation Resistance At Reference Temp:** 5000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 4.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 16 printed circuit Shelf Life:

N/a

NSN 5910-01-216-7232

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0