NSN 5910-01-217-1629

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-217-1629 **Body Style:** W/o mtg facilities, radial terminals Reliability Indicator: Not established **Terminal Length:** 25.0 millimeters **Body Diameter:** 7.0 millimeters **Body Length:** 4.0 millimeters **Center To Center Distance Between Terminals Parallel To Diameter:** 5.0 millimeters **Terminal Diameter:** 0.6 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 22.000 picofarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -60.0 to 60.0 single section **Tolerance Range Per Section:** -5.00 to 5.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 1000.0 megohms **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5910-01-217-1629

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0