NSN 5910-01-217-4021

Plastic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-217-4021 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.625 inches |
| Body Diameter: |
| 0.312 inches |
| Body Length: |
| 0.813 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Internal Electrical Connection Type: |
| Extended foil |
| Features Provided: |
| Hermetically sealed case |
| Insulation Resistance At Maximum Operating Temp: |
| 10000.0 megohms |
| Capacitance Value Per Section: |
| 6800.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| -120.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -15.0 to 15.0 single section |
| Criticality Code Justification: |
| Feat |
| Tolerance Range Per Section: |
| -5.00 to 5.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.0100 |
| Terminal Surface Treatment: |

Solder

NSN 5910-01-217-4021

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| Dielectric Material: |
|-----------------------------|
| Plastic polystyrene |
| Special Features: |
| Burn-in test |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A010b0