NSN 5910-01-217-5196

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-217-5196

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

0.250 inches 0.250 inches 0.250 inches

Body Diameter:

1.375 inches

Body Length:

2.125 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.500 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

6625-01-155-2334 counter, electro

Capacitance Value Per Section:

9500.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.045

Dc Leakage At Reference Temp:

0.005 milliamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 threaded stud

NSN 5910-01-217-5196

Electrolytic Fixed Capacitor - Page 2 of 2



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0