## NSN 5910-01-217-5197

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-217-5197

Rody	Style:
Douv	Style.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.250 inches 0.250 inches 0.250 inches

**Body Diameter:** 

1.375 inches

**Body Length:** 

3.125 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.500 inches

**Terminal Diameter:** 

0.190 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**End Application:** 

6625-01-155-2334 counter, electro

**Capacitance Value Per Section:** 

14000.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.033

Dc Leakage At Reference Temp:

0.005 milliamperes

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 threaded stud

## NSN 5910-01-217-5197

Electrolytic Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0