## NSN 5910-01-217-6980

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-217-6980

Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
1.812 inches
Body Width:
1.062 inches
Body Height:
1.625 inches
Center To Center Distance Between Terminals Parallel To Length:
0.812 inches
Terminal Diameter:
0.190 inches
Terminal Height From Body:
1.375 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
300.0 megohm-microfarads
Capacitance Value Per Section:
0.500 microfarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
1000.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
25000.0 megohms
Dielectric Material:
Paper and plastic polyethylene terephthalate
Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 standoff, threaded stud

## NSN 5910-01-217-6980

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Sp	ecit	fica	ition	Data:

81349-mil-c-19978/3 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0