

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5910-01-217-6986
Body Style:
W/mtg bracket, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.620 inches
Body Diameter:
0.460 inches
Body Length:
1.124 inches
Terminal Diameter:
0.032 inches
Unthreaded Mounting Hole Diameter:
Between 0.151 inches and 0.157 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.800 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
5000 04 445 4000 vesteres with

5820-01-145-4939 restorer, pulse

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Insulation Resistance At Maximum Operating Temp:

600.0 megohms

Capacitance Value Per Section:

0.022 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Range Per Section:

-10.00 to 10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

12000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-217-6986

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0